

# WESTERBEKE

## MARINE GENERATORS

SPECIFICATIONS	DIESEL										GASOLINE						
	4	5.0	8.0	10.0	11.0	12.5	15.0	20.0	25.0	32.0	45.0	4.5	6.5	8.5	9.0	12.5	15
KW RATINGS AT 60 HZ	4.4	5.0	8.0	10.0	11.0	12.5	15.0	20.0	25.0	32.0	45.0	4.5	6.5	8.5	9.0	12.5	15
KW RATINGS AT 50 HZ	3.3	4.0	6.0	7.5	8.25	9.3	12.5	16.0	20.0	25.0	36.0	3.5	4.8	6.8	7.0	10.0	12.0
NO. OF CYLINDERS	2	3	3	3	4	4	4	4	4	6	6	3	3	4	3	4	4
CU. IN. DISP.	37	42.47	60	68.22	80	91	128	154	182	247	346	33.4	60.6	65.4	60.6	79.1	90.9
R.P.M. 60 HZ	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800	1800
R.P.M. 50 HZ	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
LENGTH	27.2"	28.25"	28.2"	32.06"	34.56"	37.25"	38.0"	50.69"	51.12"	62.5"	67.38"	26.5"	26.75"	31.50"	28.25"	33.63"	33.63"
WIDTH	17"	16.0"	17"	17"	18"	18.17"	18.13"	22.59"	23.12"	22.21"	24.5"	18.34"	18.75"	18.75"	18.69"	18.75"	18.75"
HEIGHT	23.3"	20.53"	21.8"	22.0"	23.75"	25.34"	25.06"	27.91"	28.59"	31.0"	36.63"	23.44"	23.4"	23.63"	23.38"	23.63"	23.63"
WEIGHT	410 LB	330 LB	450 LB	495 LB	582 LB	638 LB	683 LB	910 LB	933 LB	1300 LB	1965 LB	309 LB	330 LB	513 LB	385 LB	533 LB	560 LB
F.W. COOLING	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
ELECTRIC FUEL PUMP	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
SELF-BLEEDING	STD.	STD.	STD.	STD.	STD.	STD.	STD.	NO	NO	NO	NO	N.A.*	N.A.*	N.A.*	N.A.*	N.A.*	N.A.*
EASY PRIME	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	N.A.*	N.A.*	N.A.*	N.A.*	N.A.*	N.A.*
STARTING MOTOR	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
D.C. BATTERY CHARGING	10 AMP	10 AMP	50 AMP	50 AMP	50 AMP	50 AMP	50 AMP	51 AMP	51 AMP	51 AMP	51 AMP	10 AMP	10 AMP	35 AMP	35 AMP	51 AMP	51 AMP
D.C. VOLT METER	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.
HOUR METER	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
COOLANT TEMP. GAUGE	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.
ENGINE CONTROL SYST.	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH	MECH
SAFETY SHUT-DOWNS	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
VOLTAGE REGULATION	BC	BC	BT	BT	BT	BT	BT	BE	BE	BE	BE	BC	BC	BT	BT	BT	BT
RECONNECTABLE LEAD	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
REMOTE PANEL PROV.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.	STD.
REMOTE START/STOP	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.
AUTOMATIC DEMAND	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO
SOUND ENCLOSURE	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	OPT.	NO	NO	NO	NO	NO	NO

\*4.4 WILL BE REPLACED BY 5.0 K.W. SPRING OF '89.

• Westerbeke Diesel generator sets and Marine Propulsion engines are sold through an international network of franchised Master Distributors and their dealers. Our M/D's are competent marine people who can consult and recommend from full lines without bias. Order specific descriptive brochures from them.

\*Not applicable to gasoline powered units.

- An individual may repower with Westerbeke confident of receiving that "Just Right" combination of engine, gear and accessories, or generator.
- Boatbuilders have available the help of both the Master Distributor and the Factor in developing a specification for unit or serial production at economical pricing. Make full use of your Distributor.

### VOLTAGE REGULATION KEY

- BC = Brushless Capacitor
- BE = Brushless Electronic
- BT = Brushless Transformer